

DPI 52L950J12 - 120VAC INPUT 3KVA OUTPUT DIP PROOFING INVERTER



AC INPUT

Single Phase supply voltage	120Vac 50/60Hz
Maximum input voltage	+10%
Full load current	25A

STATIC SWITCH

Nominal off-state voltage	150Vac RMS
Peak off-state voltage	800V
Nominal current(AV)	25A
Short time overload current(<100ms)	60A
Non-repetitive peak on-state current(10ms)	130A

INVERTER

Nominal output voltage	120Vac RMS
Voltage fluctuations over full operating range	-15% to +10%
Nominal Load current	25A
Power factor range	cos Φ from 1 to 0
Wave shape	Stepped Square
Nominal inductive load	3KVA
Storage capacitors(rated 200Vdc)	0.132F
Usable stored energy factor (η)	0.39
Minimum up time as a function of the load	$t = (\eta * C_{cap} * V_{supply}) / (L_{load} * \cos\Phi)$
Transistor peak current-limit	50A
Output frequency	50/60Hz +/-1%
HBC fuse rating	32A

TIMER

Range	0.1 to 3.1s
Setting	0.1s steps
Maximum recovery time of capacitors to 1,27Vin	<3 second

INDICATORS

System OK	green LED
Inverter Running	red LED

TEMPERATURE

Maximum ambient working temperature	45°C (113°F)
-------------------------------------	--------------

CUBICLE

Construction	Extruded aluminum
Height(Dim. L3 on P16)	507mm (20.28in)
Width	311mm (12.24in)
Depth	162mm (6.38in)
Mass	14.4 kg (31.68 lbs)

CONNECTION

Cable	5mm ² (10 AWG) copper panel wire
Screw-terminal torque	1.5 - 1.8 Nm (13.0-16.0 lb-in)

LISTINGS

Underwriters Laboratories Inc.	UL listed, Control #37WJ/File #E205817
--------------------------------	--

Warning:

Risk of electric shock! Dangerously high voltages can be present up to 20 minutes after DPI has been disconnected. NEVER attempt maintenance on the DPI during this period unless storage capacitors have been manually discharged.